

HIGH VOLTAGE INSULATION RESISTANCE TESTER MODEL KM 2804 IN



FEATURES

- Microprocessor controlled with advanced safety features.
- Displays and sound warning if external voltage is present.
- Battery life is extended by Enersave™ feature.
- Continuous battery monitoring.
- Auto-ranging / auto-off.
- Built-in carrying case, test leads in separate pouch.
- Real-time bargraph display on test voltage and voltage decay during discharge.
- Audible and visual message displayed if external voltage is present.
- Large LC
- Show test time duration (up to 99.9s) for easy comparison.
- IEC 1010-1 CAT. III



KM 2804 IN

1 KV 2.5 KV 5 KV 10 KV

GENERAL SPECIFICATIONS

0-250G 0-500G

MODEL KM 2804 IN

Model	0-50G	: ± 3% of reading		
Test Voltage (DC V)	50-500G	: ± 5% of reading		
Measuring Ranges (Auto-Ranges)	1030g Approx.			
Accuracy				
Dimensions	170(L)x120(W)x95(D) mm.			
Weight (battery included)				
Power Source	1.5V (AA) x 8 Batteries			
Accessories	Test leads, Shoulder belt, Instruction manual, Batteries			

Note: All Specification are Subject to change.