

HIGH VOLTAGE INSULATION RESISTANCE TESTER MODEL KM 2803 IN







FEATURES

- Displays and sound warning if external voltage is present.
- Battery life is extended by Enersave[™] feature.
- Continuous battery monitoring.
- Auto-ranging / auto-off.
- Built-in carrying case, test leads in separate pouch.
- Real-time bargraph display on test voltage and voltage decay during discharge.
- Audible and visual message displayed if external voltage is present.
- Large LC
- Show test time duration (up to 99.9s) for easy
- comparison.
- IEC 1010-1 CAT. III

GENERAL SPECIFICATIONS

Model	2803 IN			
Test Voltage (DC V)	0.5KV	1KV	2.5KV	5KV
Measuring Ranges (Auto-Ranges)	0-25GΩ	0-50GΩ	0-125GΩ	0-250GΩ
Accuracy	$0-50G\Omega$: ± 3% of reading 50-250G Ω : ± 5% of reading.			
Dimensions	170(L)x120(W)x95(D) mm.			
Weight (battery included)	930g Approx.			
Power Source	1.5V (AA) x 8 Batteries			
Accessories	Test leads, Shoulder belt, Instruction manual, Batteries			

Note: All Specification are Subject to change.



Industrial Supply Syndicate

54, Ezra Street, Kolkata - 700 001, India

Phone: 22350923, 22356676 Fax: 91-33-30222923

Email: info@industrialindia.com Website: www.industrialindia.com