



An ISO 9001:2000 Certified company

DIGITAL CLAMP METER MODEL KM 2775



Preliminary Data.

SPECIFICATIONS

AC Voltage	400.00mV \pm (2.0%rdg+3dgt) 4.000/40.00/400.0/1000V \pm (1.5%rdg+3dgt) 40 ~ 500Hz
DC Voltage	400.00mV/4.000/40.00/400.0/1000V \pm (1.0%rdg + 3dgt)
AC Current	400.0/2000A 0~1500A \pm (2.0%rdg + 4 dgt) 1500A~2000A \pm (2.5%rdg + 4 dgt)
DC Current	400.0/2000A 0~1500A \pm (2.0%rdg + 4 dgt) 1500A~2000A \pm (2.5%rdg + 4 dgt)
Ω + continuity	400.0 Ω /4.000/40.00/400.0K Ω /4.000M Ω \pm (1.5%rdg + 3dgt) 40.00M Ω \pm (2.0%rdg + 4dgt)
Hz	4.000/40.00/400.0KHz/40.00MHz \pm (0.5%rdg+2dgt)
Capacitor	4.000/40.00/400.0nF/4.000/40.00/400.0 μ F/ 4.000mF \pm (3.0%rdg + 5dgt)

FEATURES

- **Display** : 3 $\frac{3}{4}$ (4000 counts)
- **Auto-ranging**
- **Data Hold Function**
- **Low battery indication**
- **Auto Power Off**
- **Conductor Size** : 55mm Max.
- **Operating Temperature & Humidity** : -10 $^{\circ}$ C~50 $^{\circ}$ C at <80% RH
- **Power Source** : 9V battery.
- **Dimensions** : 265(L) X 100(W) X 42(D)mm
- **Weight** : 510g (battery included)
- **Accessories** : Test leads (TEL-AL28-2),
Carrying Case, Manual & battery.
- **Safety standard** : IEC/EN 61010-1 EN 61010-2
CAT III 600V
- **With Stand Voltage** : 6000V

Note: All Specifications are Subject to change



Industrial Supply Syndicate

54, Ezra Street, Kolkata - 700 001, INDIA

Phone: 22350923, 22356676 Fax: +91 33 30222923

Email: info@industrialindia.com Website: www.industrialindia.com