

# **L-MARK**<sup>®</sup> label and marke printer Lk330



## **[ Description of features ]**

- Full English operation interfaces, possible to enter English, numbers, symbols; various editing functions enabled;
- Ultra-large screen, three-line input and display; each line capable of showing 15 English letters;
- Fashionable and top-grade white background light LCD display, with status information of more than 10 functions displayed;
- Fully automatic semi-cutting or full-cutting operation;
- One-key operation: all functions can be performed by pressing only one key, thus offering a convenient and quick operation;
- International standard 85-key computer keyboard;
- Beautiful **L-MARK** font type, offering a clearer and more lasting print out;
- With a unique function of printing selected pages, enabling you to print selected pages in the current file;
- Ultra-large in-built file memory capacity, able to store more than 100 files, ready to be recalled at any time;
- **L-MARK** hi-speed computerized tube printer LK-330PC can be connected to a computer and **L-MARK** software offers new and versatile man-machine interfaces, compatible with Windows2000/XP operation systems; independent operation at the work site is possible, one machine designed for dual operations;
- Portable design, suitable to be used for various applications;
- Ribbons available in black, red, blue and white colors.



# L-MARK®

<http://www.lmark.net>



## Specifications Description

<b>Model</b>	LK-330
<b>Mode of printing</b>	Thermal transfer printing
<b>Resolution</b>	300dpi
<b>Printing character height</b>	1.3mm8mm
<b>Maximum number of input pages</b>	198
<b>Sleeve tube size printable</b>	Φ2.5-Φ6
<b>label size printable</b>	6mm, 9mm, 12mm
<b>Printing speed</b>	11.5mm/sec(with half-cut)
<b>Display</b>	LCD, white color background, displaying up to 5 lines
<b>Characters printable</b>	Chinese, English, number, symble
<b>Entry method</b>	standard 85-key
<b>Memory</b>	About 100,000 characters
<b>Material cutting method</b>	Automatic half-cutting, automatic full-cutting
<b>Power supply</b>	DC 12V 2A
<b>Ambient requirements</b>	Operation:Temp 15°C~35°C Relative humidity 10%~85% (without condensation) Storage:Temp 5°C~35°C Relative humidity 10%~85% (without condensation)
<b>Overall</b>	350(L)*290(W)*95(H)
<b>Weight</b>	About 2kg

## List of consumables provided

Product model	Product	Length (m)	Quantity/ Box
LM506WL	6mm label cassette (white)	20	5
LM509WL	9mm label cassette (white)		
LM512WL	12mm label cassette (white)		
LM506YL	6mm label cassette (yellow)		
LM509YL	9mm label cassette (yellow)		
LM512YL	12mm label cassette (yellow)		
LM506SL	6mm label cassette (silver)		
LM509SL	9mm label cassette (silver)		
LM512SL	12mm label cassette (silver)		
LM33B	Printing Ribbon (black)		
LM33W	Printing Ribbon (white)		
LM33R	Printing Ribbon (red)		
LM-02-10	Cutter (cutter holder and cutting blade)	—	2
LM-ST30W	3.0mm heat shrink tube cassette (white) (shrink ratio 2:1)	5	5
LM-ST30Y	3.0mm heat shrink tube cassette (yellow) (shrink ratio 2:1)		
LM-ST52W	5.2mm heat shrink tube cassette (white) (shrink ratio 2:1)		
LM-ST52Y	5.2mm heat shrink tube cassette (yellow) (shrink ratio 2:1)		
LM-ST68W	6.8mm heat shrink tube cassette (white) (shrink ratio 2:1)		
LM-ST68Y	6.8mm heat shrink tube cassette (yellow) (shrink ratio 2:1)		



### Contact Details

Industrial Supply Syndicate  
54, Ezra Street, Kolkata - 700 001  
Phone: 22356676 Fax: (033) 30222923  
Email: info@industrialindia.com