

TEMPERATURE / TEMPERATURE & HUMIDITY DATA LOGGER - KM-600NH

Model KM 600NH

KM 600 -NH is a new temperature / temperature and humidity and data logger with internal sensor which is widely used in cold - chain transportation field, HVAC refrigerator field, electrical industry, medical industry, as well as laboratory fields.

FEATURES :

- Up to 16000 data record point
- Resolution :
 Temperature : 0.1°C ; Humidity : 0.1%
- USB port connect to PC to browse the recording data, and generation curve, export the file with TXT / excel / format.
- Low power Indication. Real - time clock RTC, Auto dormancy and wake up function.
- Maximum / Minimum display and alarm function
- LCD Display : 43 x 33 (mm)
- Sampling time Settable
- Power supply : ER 14250 Lithium battery, 3.6 V (1000 days at standby state 3 yrs continuous on)
- Dimension : 113 x 74 x 32 (mm)
- Weight : 150g



Preliminary Data

ACCESSORIES :

User's Manual, Carrying Case, Battery installed, PC Software & USB Cable

SPECIFICATIONS :

Model	KM 600- N1	KM 600- N	KM 600- NH
Measure range	- 40 - 70°C	- 40 - 70°C	- 40 - 70°C, 0.0-99.9%
Accuracy	0.5°C	0.5°C	0.5°C / 4.0% RH
Housing	IP 40	IP 65	IP 40



All Specifications are subject to change without prior notice

Other items you might be interested in:

TRMS Power Clamp Meter KM2745



Jaw opening: 46.5 mm
 Current: 1000A AC, Voltage: 600V AC
 Active Power: 0.00 to 600.00 KW
 Apparent Power: 0.00 to 600.00 KVA
 Reactive Power: 0.00 to 600.00 KVAR
 Power Factor: -1.000 to 0.000 to +1.000
 Frequency: 20.0 to 400.0 Hz
 Harmonics: Upto 25th Order , Level of each order, % of each order and total harmonic distortion (THD-F & THD-R)
 INRUSH (100mS), HOLD and PEAK functions
 Cat III 600V

Digital TRMS Multimeter KM5040-T with bargraph



Display: 3 1/2 Digit (5000 Counts) LCD
 Current: 10Amps AC/DC
 Voltage: 1000V AC/DC
 Resistance: 50 M Ohms
 Frequency: 125 KHz
 Capacitance: 9999 uF
 hFe, Diode and continuity, Auto Power Off
 Safety: UL Approved
 Optional: RS232 Interface