PH, CONDUCTIVITY, TDS, EC WATERPROOF PEN TESTER

MODEL - 6011, 6011A, 6021, 6022, 6031, 6032, 6061



MODEL 6011/6011A



MODEL 6021



MODEL 6022



MODEL 6031



MODEL 6032



MODEL 6061

SPECIAL FEATURES :

- Fast response, reliable & accurate measurements.
- Large LCD display 21 x 18mm for easy reading.
- Impact resistant ABS case by waterproof designed IP 57 rated.
- 1 or 2 points (pH only) manual calibration via screw trim pot.
- The electrode module are changeable for replacement by user.

: APPLICATIONS :



Swimming pool & Spa



Agriculture



Fish Farming



Food Industry



Waste Water



Plating industry



Cooling Towers



Chemical Industry



Floriculture



Pharmaceutical & Medical

ACCESSORIES :

Standard solution, Battery, Screwdriver, Carrying case & instruction Manual.

ELECTRICAL SPECIFICATIONS

Functions \ Models	6011	6011A	6021	6022	6031	6032	6061
Type	**pH**	**pH**	**Conductivity**	**Conductivity**	**TDS**	**TDS**	**EC**
Range	0~14.0	0~14.00	0~19990µS/cm	0~1999µS/cm	0~19990 ppm	0~1999 ppm	0~19.99 EC
Accuracy	± 0.1+1 digit	± 0.1+1 digit	± 1% FS	± 1% FS	± 1% FS	± 1% FS	± 1% FS
Resolution	0.1 pH	0.01 pH	10 µS/cm	1 µS/cm	10 ppm	1 ppm	0.1 EC
ATC *	No	Yes	Yes	Yes	Yes	Yes	Yes
Power	3V x 2 Lithium battery CR2032						
Dimension	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm
Weight	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)

*Automatic Temperature Compensation