PROGRAMMABLE DIGITAL PANEL METER

5 DIGIT 99999 COUNTS
WATT DIGITAL PANEL METER
Model - MMW



✶ FEATURES :

- Suitable for 1ϕ 2W / 1ϕ 3W / 3ϕ 3W / 3ϕ 4W system
- 5 Digit Display : -32768 ~ +32767 Count
- Optional RS-485 Modbus RTU
- Optional DC 4 ~ 20mA output
- Bi-direction measurement & display.

ORDERING :

MMW — Code1 — Code2 — Code3 — Code4 — Code5 — Code6

Code 1	Input Voltage	Code 2	Input Current	Code 3	Input Frequency	Code 4	Output1	Code 5	Output2	Code 6	Aux. Power
1	55~440V(L-L)	1	1A	1	50 Hz	1	2 Alarm	1	RS-485	3	DC 22~72V
		2	5A	2	60 Hz	3	DC 4~20mA			6	AC/DC 85~265V
						0	None	0	None		
Y	Other	Y	Other	Y	Other	Y	Other	Y	Other	Y	Other

When ordering Specify Model, code number and variable.

Code Number : Model-code1-code2-code3-code4-code5-code6 (E.g. MMW - 12230Y)

✶ ADDITIONAL FEATURES :

- **Display Range :** 0.4" High brightness red LED 5 digit (-)32768 ~ 32767
- **Accuracy :** ± 0.5% Rdg at 23°C ± 3°C.
- **Input Range :** Input 55 ~ 440V (L-L) (Max. 500V L-L); Over Voltage 600V Continuous.
  Normal Current 5A, Effective Range 0 ~ 6A; Over Current 15A Continuous.
  Normal Current 1A, Effective Range 0 ~ 1.5A
- **Input Frequency :** 45 ~ 70Hz
- **Output Function :** 4 ~ 20mA 330Ω at 20mA (Optional)
- **Digital output Load :** RS-485 MODBUS RTU
- **Baudrate :** 2400, 4800, 9600, 19200, 38400, 57600
- **Address :** 1 ~ 255
- **Alarm Function :** 2 Alarm setting (Optional)
- **Dielectric Strength :** 2.0 KV 50/60Hz AC / Min Between Input / Power / Case.
- **Outline Dimension :** 96(W)X48(H)X100(D)mm.
- **Mounting :** Panel Flush Mounting.

5 DIGIT 99999 COUNTS
VAR (REACTIVE VOLT AMPERE)
DIGITAL PANEL METER
Model - MMQ



✶ FEATURES :

- Suitable for 1ϕ 2W / 1ϕ 3W / 3ϕ 3W / 3ϕ 4W system
- 5 Digit Display -32768 ~ 32767 count
- Optional RS-485 Modbus RTU
- Optional DC 4 ~ 20mA output
- Bi-direction measurement & display.

ORDERING :

MMQ — Code1 — Code2 — Code3 — Code4 — Code5 — Code6

Code 1	Input Voltage	Code 2	Input Current	Code 3	Input Frequency	Code 4	Output1	Code 5	Output2	Code 6	Aux. Power
1	55~440V(L-L)	1	1A	1	50 Hz	1	2 Pulse	1	RS-485	3	DC 22~72V
		2	5A	2	60 Hz	3	DC 4~20mA		ModbusRTU	6	AC/DC 85~265V
						0	None	0	None		
Y	Other	Y	Other	Y	Other	Y	Other	Y	Other	Y	Other

When ordering Specify Model, code number and variable.

Code Number : Model-code1-code2-code3-code4-code5-code6 (E.g. MMQ - 12210Y)

✶ ADDITIONAL FEATURES :

- **Display Range :** 0.4" High brightness red LED 5 Digit Display -32768 ~ 32767
- **Accuracy :** ± 0.5% RD at 23°C ± 3°C.
- **Input Range :** Input 55 ~ 440V (L-L) (Max. 500V L-L), Over Voltage 600V Continuous.
  Normal Current 5A, Effective Range 0 ~ 6A, Over Current 15A Continuous.
  Normal Current 1A, Effective Range 0 ~ 1.5A
- **Digital output Load :** RS-485 MODBUS RTU
- **Baudrate :** 2400, 4800, 9600, 19200, 38400, 57600
- **Address :** 1 ~ 255
- **Input Frequency :** 45 ~ 70Hz
- **Dielectric Strength :** 2.0 KV 50/60Hz AC / Min Between Input / Power / Case.
- **Outline Dimension :** 96(W)X48(H)X100(D)mm.
- **Mounting :** Panel Flush Mounting.