VOLTAGE TESTER

VOLTAGE TESTER
Model - KM 66

IP65

CAT III 1000V
CAT IV 600V

8KV Transient Protection



CE Approved

- ✶ **Sensing :** Average Sensing

✶ **FUNCTIONS :**

- **DC Voltage (LED) :** 12 V ~ 1000 V (12 / 24 / 50 / 120 / 230 / 400 / 690 / 1000V)
- **AC Voltage (LED) :** 12 V ~ 1000 V (12 / 24 / 50 / 120 / 230 / 400 / 690 / 1000V)

✶ **SAFETY :**

- Meets IEC/EN61010-1Ed. 3.0, IEC/EN61010-2-033Ed. 1.0, IEC/EN61243-3:2014 to CAT III 1000V & CAT IV 600V
- **E.M.C. :** Meets EN61326-1:2013
- **Pollution Degree :** 2

✶ **ADDITIONAL FUNCTIONS :**

- Non-Contact & Probe-Contact EF-Detection.
- Detachable (Black) test lead for easy replacement.
- User Replaceable Screw-On stationary (Red Probe Body)
- Automatic DCV, ACV & continuity selection.
- Audible Beeper Continuity & Visible LED indications.
- Type of protection IP65- water & dust resistant.
- Low Battery warning below approx. 2.6V
- **Auto Power Off** : Resistance and Capacitance functions: Idle for 8 seconds & Other functions 16 seconds.
- Rugged fire retarded casing.

✶ **Power supply :** Alkaline 1.5V AAA Battery x 2.
✶ **Weight :** Approx. 235gm. with holster.
✶ **Dimension :** Approx. 278(L) x 57(W) x 40(H)mm.
✶ **Accessories :** Test lead pair, Battery, User Manual & Carrying case.

3½ DIGIT 1999 COUNTS VOLTAGE TESTER
Model - KM 69

IP65

CAT III 1000V
CAT IV 600V

8KV Transient Protection



CE Approved

- ✶ **Sensing :** TRMS
- ✶ **DC Voltage Basic Accuracy :** 1.0%
- ✶ **LCD Display :** 3½ Digit 1999 counts
- ✶ **Update :** 5 per second

✶ **FUNCTIONS :**

- **DC Voltage (LCD Display) :** 0.1V ~ 1000V (12 / 24 / 50 / 120 / 230 / 400 / 690 / 1000V)
- **AC Voltage (LCD Display) :** 0.1V ~ 1000V (12 / 24 / 50 / 120 / 230 / 400 / 690 / 1000V)

✶ **SAFETY :**

- Meets IEC/EN61010-1Ed. 3.0, IEC/EN61010-2-033Ed. 1.0, IEC/EN61243-3:2014 to CAT III 1000V & CAT IV 600V
- **E.M.C. :** Meets EN61326-1:2013
- **Pollution Degree :** 2

✶ **ADDITIONAL FUNCTIONS :**

- AC Detection Shaker & RCD leakage-path
- RST Phase Rotation Detection & sequence.
- Non-Contact & Probe-Contact EF-Detection.
- Detachable (Black) test lead for easy replacement.
- User Replaceable Screw-On stationary (Red Probe Body)
- Automatic DCV, ACV & Audible continuity selection.
- RCD Leakage load for 230V AC / 30mA RCD Circuit Breakers.
- Audible Beeper Continuity & Visible LED indications.
- Display Backlight & flash-light for easy viewing in the dark
- Type of protection IP65- water & dust resistant.
- Low Battery warning below approx. 2.6V
- **Auto Power Off** : Resistance and Capacitance functions: Idle for 8 seconds & Other functions 16 seconds.
- Rugged fire retarded casing.

✶ **Power supply :** Alkaline 1.5V AAA Battery x 2.
✶ **Weight :** Approx. 235gm. with holster.
✶ **Dimension :** Approx. 278(L) x 57(W) x 40(H)mm.
✶ **Accessories :** Test lead pair, Battery, User Manual & Carrying case.

NON-CONTACT AC VOLTAGE DETECTOR
Model - KM 6190

IP67

CAT IV 600V
CAT III 1000V



CE Approved

✶ **FUNCTIONS :**

- **Dual range Non-contact AC voltage Detector**
- **AC Voltage Detection :** 12V ~ 1000V / 48V ~1000V
- **Alarm mode : Sound & light indication**
- Hot line & Netural line distinguish
- White LED Flashlight for dark area
- **Adjustable sensitivity.**
- **2m drop-proof**
- **IP67 waterproof**
- **Strong ABS plastic case.**
- Zero / Fire wire test : tested from the signal strength the fire wire has strong signal.

✶ **Power supply :** 1.5V AAA X 2 battery.
✶ **Dimension :** Approx. 156 x 20 x 20 mm.
✶ **Weight :** Approx. 45 gm.
✶ **Accessories :** User Manual, battery & Blister case.