PROFESSIONAL & INDUSTRIAL GRADE DIGITAL CLAMPMETERS

AC / DC AUTORANGING DIGITAL CLAMPMETER Model - KM 2720

CAT II 600V
CAT III 300V



CE Approved

- ✶ **Sensing :** Average sensing
- ✶ **Jaws Opening size :** 23 mm Max.
- ✶ **Display :** 3¾ digits 3999 counts LCD display .
- ✶ **Over Range :** Display "OL"

✶ **FUNCTIONS :**

- **AC / DC Current :** 10 mA ~ 200 .0A.
- **AC Voltage :** 100 µV ~ 750 V.
- **DC Voltage :** 100 µV ~ 1000 V.
- **Resistance :** 100 mΩ ~ 40.00 MΩ.
- **Frequency :** 0.001 Hz ~ 9.999 MHz.
- **Capacitance :** 10 pF ~ 40.00 µF.
- **Duty Cycle :** 0.1 % ~ 99.9 %.

✶ **ADDITIONAL FUNCTIONS :**

- Data Hold function
- Auto Zero adjustment
- Auto Polarity display
- Low Battery Indication & Auto Power Off.
- Diode & Continuity Test.

✶ **Power supply :** 1.5V AA battery x 2

✶ **Weight :** Approx.180 gm.

✶ **Dimension :** Approx. 183(L) X 43(W) X 31(H) mm

✶ **Accessories :**Test leads, User Manual, Battery & Carrying Case.

AC / DC AUTORANGING DIGITAL CLAMPMETER Model - KM 2725

CAT II 600V
CAT III 300V



CE Approved

- ✶ **Sensing :** Average sensing
- ✶ **Jaws Opening size :** 23 mm Max.
- ✶ **Display :** 3¾ digits 3999 counts LCD display .
- ✶ **Over Range :** Display "OL"

✶ **FUNCTIONS :**

- **AC / DC Current (KM 2725) :** 1 mA ~ 40.00 A.
- **AC Voltage :** 100 µV ~ 750 V.
- **DC Voltage :** 100 µV ~ 1000 V.
- **Resistance :** 100 mΩ ~ 40.00 MΩ.
- **Frequency :** 0.001 Hz ~ 9.999 MHz.
- **Capacitance :** 10 pF ~ 40.00 µF.
- **Duty Cycle :** 0.1 % ~ 99.9 %.

✶ **ADDITIONAL FUNCTIONS :**

- Data Hold function
- High resolution DCA / ACA of 1mA.
- Auto Zero adjustment
- Auto Polarity display
- Low Battery Indication & Auto Power Off.
- Diode & Continuity Test.

✶ **Power supply :** 1.5V AA battery x 2

✶ **Weight :** Approx.180 gm.

✶ **Dimension :** Approx. 183(L) X 43(W) X 31(H) mm

✶ **Accessories :**Test leads, User Manual, Battery & Carrying Case.

4-20mA DC PROCESS CLAMPMETER Model - KM 071

Measures 4-20mA DC Without Breaking The Electrical Circuit

Small Jaw easy to reach any place



CE Approved

- ✶ **Jaws Opening size :** 5mm Max.

✶ **FUNCTIONS :**

- **DC Current :** 0.01 mA ~ ± 40.00 mA DC.
- **Percentage Span :**

20 mA DC : 100 %
16 mA DC : 75 %
12 mA DC : 50 %
8 mA DC : 25 %
4 mA DC : 0 %
3.6 mA DC : -2.5 %
3.2 mA DC : -5.0 %
2 mA DC : -12.5 %

✶ **ADDITIONAL FUNCTIONS :**

- DC mA measurement (4 - 20 mA); 0 - 40 mA.
- Auto Zero & Data Hold function.
- Percentage span (0-100%)
- Backlight display
- Measurement spotlight LED
- Low Battery Indication.

✶ **Power supply :** 9V battery, IEC Lr6.

✶ **Weight :** Approx. 260 gm.

✶ **Dimension :** Approx. 59(W) x 38(H) x 212(L)mm.

✶ **Accessories :** User Manual, Battery & Carrying case.