PROFESSIONAL & INDUSTRIAL GRADE DIGITAL CLAMPMETERS

1000A AC TRMS DIGITAL CLAMPMETER Model-KM 3060-T



CAT II 600V

CE Approved

- **Sensing :** TRMS sensing
- **Jaws Opening size :** Φ40mm
- **Display :** 3-5/6 digits 6000 counts LCD Backlight display. Automatic indication of functions and symbols.

FUNCTIONS :

- **AC Current :** 0.01A ~ 1000A
- **DC Voltage :** 0.1mV ~ 1000V
- **AC Voltage :** 0.1mV ~ 750V
- **Frequency :** 10Hz ~ 10MHz
- **Resistance :** 0.1Ω ~ 60MΩ
- **Capacitance :** 0.01 nF ~ 100mF
- **Temperature :** -20°C ~ 400°C; 400°C ~ 750°C

ADDITIONAL FUNCTIONS :

- Date Hold Function.
- Over range indication.
- Maximum Voltage between any terminal & Earth ground 750 Vrms .
- Altitude upto 2000 meters & Indoor use only
- Relatively humidity 80% max.
- Low Battery indication.
- Auto Power Off after 15 miinutes
- Diode & Continuity test

- **Power supply :** 1.5V x 2 AA battery.
- **Weight :** Approx.465 gm.
- **Dimension :** Approx. 228(L) x 75(W) x 36(H) mm
- **Accessories :**Test leads, User Manual, Battery & Carrying Case.

1000A AC DIGITAL CLAMPMETER Model-KM 3060



CAT II 600V

CE Approved

- **Sensing :** Average sensing
- **Jaws Opening size :** Φ40mm
- **Display :** 3 ½ digits 2000 counts LCD Backlight Display.

FUNCTIONS :

- **AC Current :** 0.01A ~ 1000A
- **DC Voltage :** 1V ~ 1000V
- **AC Voltage :**1V ~ 750V
- **Frequency :** 1Hz ~ 2KHz
- **Resistance :** 0.1Ω ~ 2MΩ

ADDITIONAL FUNCTIONS :

- Data Hold Function.
- Low Battery indication.
- Overrrange indication.
- Auto Power Off.
- Diode & Continuity test

- **Power supply :** Standard 9V battery.
- **Weight :** Approx.465 gm.(including battery)
- **Dimension :** Approx. 228(L) x 75(W) x 36(H) mm
- **Accessories :**Test leads, User Manual, Battery & Carrying Case.

600A AC / DC TRMS DIGITAL CLAMPMETER Model - KM 2732

NEW



CAT III 600V DC/AC

CE Approved

- **Sensing :** TRMS sensing
- **Jaws Opening size :** 26mm Max.
- **Display :** 3⅝ digits 6000 Counts Backlight LCD display.

FUNCTIONS :

- **AC / DC Current :** 0.01A ~ 600A
- **DC Voltage :** 0.1mV ~ 600V
- **AC Voltage (TRMS) :** 0.001V ~ 600V
- **Resistance :** 0.1 Ω ~ 60 MΩ.
- **Capacitance :** 0.001 nF ~ 60 mF.
- **Frequency:** 0.01Hz ~ >1kHz
- **Passing the Hz% Switch:** 0.01Hz ~ 9.999MHz
- **Temperature :** -50 °C ~ 1300 °C
- **Duty Cycle :** 0.1 ~ 99.9%

SAFETY :

- IEC61010-1, IEC61010-2-032 CAT III 600V

ADDITIONAL FUNCTIONS :

- Automatic selection of measuring function & range.
- Full range overload protection
- The maximum allowable voltage between the measuring terminal & the ground is 600VDC or 600VAC
- **Hyperview display :** 'OL' or '-OL'.
- **Unit display :** with function, unit display of electricity.
- Auto Power Off in 15 minutes
- Low battery indication
- Diode Test, Continuity Test

- **Power supply :** 1.5V AAA x 2 battery.
- **Weight :** Approx. 200 gm. (Including battery)
- **Dimension :** Approx.185(L) x 71(W) x 35(H)mm.
- **Accessories :** Test leads (pair), User's manual, Battery, Bead type Thermocouple upto 250°C & Carrying case.