PROFESSIONAL & INDUSTRIAL GRADE DIGITAL CLAMPMETERS

300A AC DIGITAL CLAMPMETER Model - 2700

India's Largest Selling Clampmeter Since 30 Yrs.



CE Approved

- **Sensing :** Average Sensing
- **Jaw Opening :** 32mm Max.
- **Display :** 3½ digits 2000 counts LCD display with automatic sign & functions.

FUNCTIONS :

- **AC CURRENT :** 0.01 A ~ 300 A
- **AC Voltage (50Hz ~ 500Hz) :** 0.1 V ~ 750 V.
- **DC Voltage :** 1 mV ~ 1000 V
- **Resistance :** 0.1 Ω ~ 200 KΩ.

ADDITIONAL FUNCTIONS :

- Large LCD for easy reading.
- Data Hold switch freezes reading.
- Instant continuity buzzer.
- Overload protection on all ranges.
- Low Battery Indication.
- Diode Test & Continuity Test.

- **Power supply :** 1.5V x 2 AA / Standard 9V battery.
- **Weight :** Approx. 250 gm.(including battery)
- **Dimension :** Approx. 192(L) x 82(W) x 33(H) mm.
- **Accessories :** Test leads (pair), Battery, User manual, Carrying case & Drop proof wrist strap.

100A AC/DC TRMS DIGITAL CLAMPMETER Model - KM 2730

NEW

CAT III 600V



CE Approved

- **Sensing :** TRMS sensing
- **Jaws Opening size :** 25mm Max.
- **Display :** 3½ digits 1999 Counts Backlight LCD display.

FUNCTIONS :

- **AC / DC Current :** 0.001A ~ 100A
- **DC Voltage :** 0.1mV ~ 600V
- **AC Voltage :** 0.001V ~ 600V
- **Resistance :** 0.1 Ω ~ 20 MΩ.
- **Capacitance :** 0.1 nF ~ 2000 µF.
- **Temperature :** -20 °C ~ 1000 °C

ADDITIONAL FUNCTIONS :

- Highly reliable & precise & Easy to carry.
- Autoranging
- Reading Hold
- Full range overload protection.
- Non-Contact Voltage Detection
- Auto Power Off in 15 minutes
- Low battery indication
- Diode Test, Continuity Test

- **Power supply :** 1.5V AAA x 2 Battery.
- **Weight :** Approx. 140 gm. (Including battery)
- **Dimension :** Approx 165 (L) x 56 (W) x 31 (H) mm.
- **Accessories :** Test leads (pair), User's manual, Battery, Thermocouple & Carrying case.

600A AC/DC TRMS DIGITAL CLAMPMETER Model - KM 2733

NEW

CAT III 600V AC/DC



CE Approved

- **Sensing :** TRMS sensing
- **Jaws Opening size :** 28mm Max.
- **Display :** 3 5/6 digits 6000 Counts Backlight LCD display.

FUNCTIONS :

- **AC (1kHz) / DC Current :** 0.01A ~ 600A
- **DC Voltage :** 0.1mV ~ 600V
- **AC Voltage (1kHz) :** 0.001V ~ 600V
- **Resistance :** 0.1 Ω ~ 60 MΩ.
- **Capacitance :** 0.1 nF ~ 60 mF.
- **Frequency :** 0.001 Hz ~ 9.999MHz
- **Duty Cycle :** 0.1 ~ 99.9 %
- Diode & Continuity Test

SAFETY :

- IEC61010-2-032 CAT III 600V

ADDITIONAL FUNCTIONS :

- Max. input Voltage between input & socket & the earth 600VRMS
- Double Integral A/D convertor
- Auto ranging
- Over range indication
- Non-Contact Voltage Detection
- Backlight display & Flashlight
- Data Hold Function
- Low battery indication

- **Power supply :** 1.5V AAA x 3 battery.
- **Weight :** Approx. 230 gm. (Including battery)
- **Dimension :** Approx.218(L) x 84(W) x 41(H)mm.
- **Accessories :** Test leads (pair), User's manual, Battery, & Carrying case.