PHASE ROTATION TESTER WITH VOLTMETER
Model - KM 885PR



CE Approved

✷ **Display :** 6000-count LCD display voltmeter

✷ **FUNCTIONS :**

- **3 functions in one unit :** Phase Rotation, Phase Presence, Voltmeter.
- **Voltage range :** 75 ~ 600V AC
- **Frequency Range :** 40 ~ 400Hz
- **Time limit :** 40 ~ 400 seconds

AC Voltage (Autoranging)

Range	Resolution	Accuracy
600 mV	0.1 mV	±(2.3% rdg + 5dgts)
6 V	1 mV	
60 V	10 mV	
600 V	0.1 V	

DC Voltage (Autoranging)

Range	Resolution	Accuracy
600 mV	0.1 mV	±(0.8% rdg + 3dgts)
6 V	1 mV	
60 V	10 mV	
600 V	0.1 V	

✷ **SAFETY :**

- Comply with EN61010-1 CAT III 600V; EN61326-1

✷ **ADDITIONAL FUNCTIONS :**

- **LCD contract type Phase Rotation Tester**
- **Large LCD to show phase rotation & phase presence.**
- **Check a wide range of three phase power sources.**
- **Circuit Structure :** All electronic
- Data Hold function
- Auto ranging Voltmeter AC/DC
- Auto power off

✷ **Power Supply :** 1.5V (AAA) battery x 2

✷ **Weight :** approx. 245 g.

✷ **Dimension :** 165(L) × 82(W) × 45(D) mm

✷ **Accessories :** User Manual, Batteries, Test Leads & Carrying case.

PHASE SEQUENCE METER CONTACT TYPE
Model - KM 855PR

CAT IV 600V



CE Approved

✷ **FUNCTIONS :**

- **Measuring Voltage Range :** 200V ~ 600V AC.
- **Withstand Voltage :** 1,500V AC for one minute.
- **Measuring frequency range :** 50Hz ~ 60Hz.
- **Time limit for continuous measurement :** 60 min. at 200V AC, 4 min. at 600V AC.

✷ **SAFETY :**

- EN61010-1 EN61010-2-31 CAT IV 600V.

✷ **ADDITIONAL FUNCTIONS :**

- Two functions in one unit.
- It is used to measure the Phase sequence (R,Y,B) & Open phase Condition through LED and Buzzer.
- **Cord :** 1.1 m each of Red(R), White(S) & Black(T) cord.
- Pollution degree 2
- Large size alligator chips

✷ **Dimension :** Approx. 134 x 84 x 45 mm (excluding the measuring lead)

✷ **Weight :** Approx. 530 g.

✷ **Accessories :** Test leads with Insulated Crocodile clips, User Manual & carrying case.